

CS43

4 X 3" + 2 x 1.2" Column Array Loudspeakers

Features

The CS Series CS43 is equipped with 4 x 3" woofers, 2 x 1.2" dome tweeters, and a low-inductance passive crossover. It can handle 120W RMS and 240W program power output at 8-ohm, delivering balanced and crisp audio throughout any small to medium-sized venues. Constructed of an aluminum enclosure, the CS43 is built to withstand the elements. Its weather-resistant construction protects against dust and water, making it an ideal choice for outdoor installations and high-humidity environments. Combined with the speaker's versatile mounting options, the connectors with a waterproof cover, make it a reliable and flexible solution for both permanent and temporary audio setups.

With direct radiating drivers built in, the column speaker has a 140° x 25° coverage. Even better, it comes with a standard wall mount bracket and there is also a four direction adjustable bracket with 0~10° of vertical, ± 90° of horizontal (STCL-AB, sold separately) which allows you to tilt the angle of the loudspeaker for optimal focusing on the listening area. Optional adapter STCL-POLESET is available for stand pole set up. Featuring both Speakon and EUROBLOCK connectors, the CS43 can be used as an installation speaker or a portable PA system. It is well-suited for a wide range of applications, including live stage performances, church services, conference centers, nightclubs, restaurants, and lounges.



Technical Specifications

Frequency Response	102Hz - 20000Hz (± 3dB) 85Hz - 20000Hz (-10dB)
Power Rating	120 W-240 W PP @ 8 OHM
Driver	4x3" + 2 x1,2" dome tweeter
Maximum SPL	123 dB SPL peak
Weight	4,8 kg
Connection	Speakon-Euroblock connectors
Enclosure	Extrusion Aluminum
IP rate	IP 55-22C-+55C
Finish	Black & White water-based paint
Dispersion Angle	H 140 x V 25 degree
Dimensions	111 X 98 X 485 mm