

## CS 43

### 4 X 3" + 2 X 1,2" COLUMN ARRAY LOUDSPEAKER

#### Features

The CS Series CS43 is equipped with 4 x 3" woofers, 2 x 1.2" dome tweeters, and a low-inductance passive crossover. It can handle 120W RMS and 240W program power output at 8-ohm, delivering balanced and crisp audio throughout any small to medium-sized venues. Constructed of an aluminum enclosure, the CS43 is built to withstand the elements. Its weather-resistant construction protects against dust and water, making it an ideal choice for outdoor installations and high-humidity environments. Combined with the speaker's versatile mounting options, the connectors with a waterproof cover, make it a reliable and flexible solution for both permanent and temporary audio setups. With direct radiating drivers built in, the column speaker has a 140° x 25° coverage. Even better, it comes with a standard wall mount bracket and there is also a four direction adjustable bracket with 0~10° of vertical, ± 90° of horizontal (CLS sold separately) which allows you to tilt the angle of the loudspeaker for optimal focusing on the listening area. Optional adapter CLP is available for stand pole set up. Featuring both Speakon and EUROBLOCK connectors, the CS43 can be used as an installation speaker or a portable PA system. It is well-suited for a wide range of applications, including live stage performances, church services, conference centers, nightclubs, restaurants, and lounges.



#### Technical Specifications

| Feature            | Specification                                    |
|--------------------|--|
| Frequency Response | 102Hz – 20000Hz (± 3dB) / 85Hz – 20000Hz (-10dB) |
| Power Rating       | 120 W-240 W PP @ 8 OHM                           |
| Driver             | 4x3" + 2 x1,2" dome tweeter                      |
| Maximum SPL        | 123 dB SPL peak                                  |
| Weight             | 4,8 kg   |
| Connection         | Speakon-Euroblock connectors                     |
| Enclosure          | Extrusion Aluminum                               |
| IP Rate            | IP 55 -22C to +55C                               |
| Finish             | Black & White water-based paint                  |
| Dispersion Angle   | H 140 x V 25 degree                              |
| Dimensions         | 111 X 98 X 485 mm                                |