

# CS 103

## 10 X 3" + 6 X 1.2" COLUMN ARRAY LOUDSPEAKER

### Features

The CS SERIES is equipped with 10 x 3" woofers, 6 x 1.2" dome tweeters, and a low-inductance passive crossover. It can handle 300W RMS and 600W program power output at 8-ohm, delivering balanced and crisp audio throughout any small to medium-sized venues. Constructed of an aluminum enclosure, the CS103 is built to withstand the elements. Its weather-resistant construction protects against dust and water, making it an ideal choice for outdoor installations and high-humidity environments. Combined with the speaker's versatile mounting options, the connectors with a waterproof cover, make it a reliable and flexible solution for both permanent and temporary audio setups. With direct radiating drivers built in, the column speaker has a 140° x 25° coverage. Even better, it comes with a standard wall mount bracket and there is also a four direction adjustable bracket with 0~10° of vertical, ± 90° of horizontal (STCL-AB, sold separately), which allows you to tilt the angle of the loudspeaker for optimal focusing on the listening area. Optional adapter **STCL-POLESET** is available for stand pole installation. Featuring both Speakon and EUROBLOCK connectors, the CS103 can be used as an installation speaker or a portable PA system. It is well-suited for a wide range of applications, including live stage performances, church services, conference centers, nightclubs, restaurants, and lounges.



### Technical Specifications

Feature	Specification
Frequency Response	100Hz – 20000Hz (± 3dB) / 80Hz – 20000Hz (-10dB)
Power Rating	300 W – 600 W @ 8 OHM
Driver	10 x 3" + 6 x 1.2" Dome Tweeter
Maximum SPL	127 dB SPL peak
Weight	10.3 kg
Connection	SpeakON – Euroblock Connectors
Enclosure	Extrusion Aluminum
IP Rate	IP55 (-22°C to +55°C)
Finish	Black & White Water-Based Paint
Dispersion Angle	140° H x 25° V
Dimensions	111 x 98 x 1200 mm