

D4600T

4 X 600 W @100 V DSP AMPLIFIER

Applications

- * Stadium, School, Meeting Room, Airport Terminal
- * Hotel, Restaurant, Coffee Bar, Shopping Mall etc.



Technical Specifications

Model:	D4600T
Output Power (100V line)	600W x 4
Output Power (70V line)	600W x 4
Input sensitivity	0.9-1.1V (0 ± 1dBV)
Input Impedance	20k (balanced), 10k (unbalanced)
Frequency response	100 Hz – 15 kHz
Voltage gain (100V)	40 dB
THD + N	<0.1%
S/N rate	>95 dB
Crosstalk	>70 dB
Damping factor	>200
Power output circuitry	Switching power, Class-D
Power supply	AC 110V~120V or 220V~240V, 50/60 Hz
Protections	Short circuit, open circuit, thermal, ultrasonic and RF
Connectors	INPUT & OUTPUT: Euroblock
Controls	Front: AC switch, Input level control for each channel Rear: 70V / 100V selector optional Dante
Indicators	SIGNAL: green LED CLIP: red LED POWER: green LEDPROTECTION: red LED PRIOR:green / red LED
Dimensions(WxDxH)	483 x 44 x 360 (mm) / 19 x 1.73 x 14.17 (inch)
Weight(Lbs)	6.3kg / 13.9 lbs