

LX108

SINGLE 8" PASSIVE FULL RANGE SPEAKER.

Features

- * 8" LF with 2" voice coil, 1.4" titanium compression driver.
- * High grade plywood with quality texture coating available in black and white.
- * U bracket included for installation.
- * Used in meeting room, multi-function hall, bar, museum, church, KTV etc.



Technical Specifications

Feature:	Specification
Frequency Response:	65 Hz – 20kHz
Sensitivity	96 db
Spl Max:	128 db
Dispersion:	100° x 55° (H x V) Horn rotatable
Loudspeaker Data:	
Configuration:	8" multi-angle full range loudspeaker
Transducer:	LF: 1 x 8", HF: 1 x 1.4" diaphragm
Impedance:	8Ω Nominal
Power Handling	350 / 700W
Connectors:	2 x 4 Pin Speakon®, Barrier Strip
Physical:	
Cabinet Construction:	High grade 100% birch plywood
Mounting:	M8 inserts / U bracket
Finish:	Texture coating (RAL colors available)
Grill And Rigging Component:	Steel with anti-corrosion coat
Dimensions (mm / Inch):	250 W – 230 D – 445 H / 9.8 W – 9.1 D – 17.5 H
Weight:	9 kg / 19.8 lb