

# THEATRE 200 RGBW

## 200 W RGBW LED PROFILE SPOT

### Features

THEATRE 200 RGBW, 200W RGBW COB LED Profile Spot. Color temperature: 2000K–8000K. Beam angle: 12°–30°, optional lenses: 12°/19°/26°/30°/36°/50°. 5–10 DMX channels, 7 dimming curves, 0–100% linear dimming. PowerCON input, 3P-XLR DMX512. IP20, die-cast aluminum housing. Size: 750×350×350mm. Weight: 7kg.



### Technical Specifications

| Feature                          | Specification                                                                                                                                                                        |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Signal input / output:           | 3P-XLR input / output, DMX512 signal                                                                                                                                                 |
| Power consumption:               | 200W maximum                                                                                                                                                                         |
| Color:                           | 2000 K-8000 K                                                                                                                                                                        |
| Luminos angle:                   | 12 ° / 19 ° / 26 ° / 30 ° / 36 ° / 50 ° (optional)                                                                                                                                   |
| LED light source:                | 200 W COB LED-RGBW                                                                                                                                                                   |
| Control:                         | RGBW 7 dimming curves can be selected; master-slave synchronization; separate self-propelled program,0%-100% linear dimming,Dmx mode, Color change,color fade,static color,auto mod. |
| DMX channel:                     | 5-10 channel -95 Color rendering Index ,DMX                                                                                                                                          |
| Beam angle:                      | 12-30°                                                                                                                                                                               |
| Waterproof rating:               | IP20                                                                                                                                                                                 |
| Housing material:                | die-cast aluminum                                                                                                                                                                    |
| Power input:                     | PowerCON power                                                                                                                                                                       |
| Working environment temperature: | -25°-55°                                                                                                                                                                             |
| Voltage adp:                     | Ac/Dc15V                                                                                                                                                                             |
| Size:                            | 750*350*350mm                                                                                                                                                                        |
| N.W:                             | 7 kgs                                                                                                                                                                                |